



UNITED GX

Product Description:

United GX Fully Synthetic Engine Oil is a new fully synthetic passenger car motor oil (PCMO) that delivers the latest development in lubricating oil technology to maximize the protection for the newest engine fueled by gasoline. It meets the highest API SN performance level and exceeds most demanding requirements in relation to modern engine's emission control as well as oil consumption. In the energy-conscious era of today, United GX Fully Synthetic Engine Oil also designed to improve fuel efficiency by saving consumers on the cost of fuel.

Applications / Benefits:

- ▣ Silk smooth operation for all high performance engines.
- ▣ Exceed the highest U.S. standards for gasoline and LPG/CNG engines.
- ▣ Emission system durability and fuel economy.
- ▣ Piston Cleanliness and engine sludge protection
- ▣ Wear protection and extended service life.

Typical Characteristics:

Test Description	Method	5W30*	0W40	5W40	10W40
SAE Viscosity Grade	SAE J 300	5W30*	0W40	5W40	10W40
Specific Gravity @ 15 °C	ASTM D 4052	0.850	0.851	0.885	0.897
Flash Point, °C	ASTM D 92	210	212	216	220
Pour Point, °C	ASTM D 97	-39	-42	-39	-36
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	67.2	79.5	89.9	98.4
cSt @ 100°C	ASTM D 445	11.2	14.2	14.5	14.6
Viscosity Index	ASTM D 2270	160	186	168	155
TBN, mgKOH/g	ASTM D 2896	7.8	7.8	7.8	7.8
Color	ASTM D 1500	<3.0	<3.0	<3.0	<3.0

Specifications, Approvals & Recommendations:

- API SN
- ILSAC GF-5

*Please note official claim apply to SAE 5W30, only

Product Data Sheet