



## UNITED POWER XTG 9

### Product Description:

United Power XTG-9 is formulated with the most advanced additive components for its class, protecting engines from the stress of cold starts as well as short trip driving. It provides high temperature protection in all grades, exceeding the toughest standards against thermal breakdown.

### Applications / Benefits:

- ▣ Formulated for stop and go driving.
- ▣ Protects against rust and corrosion.
- ▣ Exceeds the highest U.S. standards for automotive engine wear protection.
- ▣ Protects engines under severe driving conditions.
- ▣ Eliminates the need for extra oil additives.

### Typical Characteristics:

Test Description	Method	10W-40	15W-40	15W-50	20W-50
SAE Viscosity Grade	SAE J 300				
Specific Gravity @ 15 °C	ASTM D 4052	0.876	0.886	0.885	0.892
Flash Point, °C	ASTM D 92	210	230	228	238
Pour Point, °C	ASTM D 97	-27	-24	-24	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	95.7	110	141	175
cSt @ 100°C	ASTM D 445	14.5	14.6	18.0	18.8
Viscosity Index	ASTM D 2270	157	137	145	121
TBN, mgKOH/g	ASTM D 2896	5.2	5.2	5.2	5.2
Color	ASTM D 1500	3.0	3.0	3.0	3.0

### Specifications, Approvals & Recommendations:

- API SJ
- JASO MA2