



UNITED LPG/CNG

Product Description:

United LPG/CNG Engine Oil is a multi-function lubricant designed specially for vehicles burning gas as the fuel. It contains a balanced blend of select high performance, high viscosity index hydrocracked base stocks and a special proprietary anti-oxidation additive package that ensure it works perfectly in the usually red hot gas engine because of burning fuel gas.

United LPG/CNG Engine Oil is also a perfect choice for any other gasoline engine which requires outstanding high temperature performance.

Applications / Benefits:

- ▣ Reduces engine wear and extends engine life.
- ▣ Protects engine under high temperature operating conditions.
- ▣ Retards harmful deposit formation on vital engine parts.
- ▣ Protects against rust and corrosion.

Typical Characteristics:

Test Description	Method	10W30	10W40	15W40	15W50	20W50
SAE Viscosity Grade	SAE J 300					
Specific Gravity @ 15 °C	ASTM D 4052	0.877	0.878	0.885	0.886	0.893
Flash Point, °C	ASTM D 92	220	218	228	228	232
Pour Point, °C	ASTM D 97	-27	-27	-24	-24	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	73.7	96.6	106.4	141	192.2
cSt @ 100°C	ASTM D 445	11.3	14.4	14.5	18.2	20.5
Viscosity Index	ASTM D 2270	145	154	140	145	124
TBN, mgKOH/g	ASTM D 2896	6.5	6.5	6.5	6.5	6.5
Color	ASTM D 1500	<2.5	<2.5	<2.5	<2.5	<2.5

Specifications, Approvals & Recommendations:

- API SL
- ACEA B2-98 Issue 2