



UNITED RECREATIONAL WATERCRAFT

Product Description:

United Recreational Watercraft 4-T, SAE 10W40 is specially formulated with rust and corrosion inhibitors to meet unique rust and general performance engine test requirements associated with the NMMA FC-W specification.

With the superior water separation ability plus a high technology core additive package, United Recreational Watercraft 4-T, SAE 10W40 is ideal to be used in watercraft 4-T engines where optimal supercharged engine clutch performance as well as other unique requirements are essential.

United Recreational Watercraft 4-T, SAE 10W40 meet the requirements of API SL.

Applications / Benefits:

- ▯ Specifically formulated for watercraft 4T engine.
- ▯ Satisfying the unique watercraft engine demands.
- ▯ Exceeds very high API gasoline engine performance as well.

Typical Characteristics:

Test Description	Method	
SAE Viscosity Grade	SAE J 300	10W40
Specific Gravity @ 15 °C	ASTM D 4052	0.874
Flash Point, °C	ASTM D 92	212
Pour Point, °C	ASTM D 97	-33
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	93.3
cSt @ 100°C	ASTM D 445	14.2
Viscosity Index	ASTM D 2270	157
TBN, mgKOH/g	ASTM D 2896	6.9
Color	ASTM D 1500	<3.0

Specifications, Approvals & Recommendations:

- API SL
- NMMA FC-W