



UNITED ATF LT

Product Description:

United ATF LT is a premium synthetic automatic transmission fluid. It is formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes. United ATF LT can be used in a broad range of automatic transmission standards and provides excellent service in a wide variety of North American, European, and Asian vehicles. It's particularly suitable for 4 and 5 speeds automatic transmissions.

United ATF LT is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A, Ford M and Allison C-4 fluid specifications and suitable for use in automatic transmission recommending Toyota Type T-IV.

Applications / Benefits:

- ▣ Provides excellent oxidation and thermal stability for longer life.
- ▣ Superior wear protection to protect critical transmission components.
- ▣ Excellent viscosity stability(high VI), application in a wide variety of Auto Transmission.
- ▣ Excellent friction and anti-shudder performances, improve driver's comfort with smooth and efficient shifting.
- ▣ Much enhanced fluidity at very low temperature service.
- ▣ Excellent rust and corrosion protection.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.853
Flash Point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	38.1
cSt @ 100°C	ASTM D 445	7.24
Viscosity Index	ASTM D 2270	157
Color	ASTM D 1500	<2.5

Specifications, Approvals & Recommendations:

Esso LT 71141

SFU

Product Data Sheet