



UNITED ATF WS

Product Description:

United ATF WS is a premium synthetic automatic transmission fluid. It is formulated with selected synthetic base stocks and latest additive technology available that provides excellent service in applications calling for low viscosity ATF, such as: Toyota Type WS.

Synthetic base stocks and stability of United ATF WS protects against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -45° C. Moreover, it improves overall transmission durability and cleanliness.

Applications / Benefits:

- ▣ Provides excellent oxidation and thermal stability for longer life.
- ▣ Superior wear protection to protect critical transmission components.
- ▣ Excellent viscosity stability (high VI), application in low viscosity Auto Transmission.
- ▣ Much enhanced fluidity at very low temperature.
- ▣ Excellent rust and corrosion protection.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.845
Flash Point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	26.72
cSt @ 100°C	ASTM D 445	5.66
Viscosity Index	ASTM D 2270	160
Appearance	Visual	Red

Specifications, Approvals & Recommendations:

- Toyota / Lexus / Scion Type WS SFU

SFU = Suitable for Use