

UNITED MX SUPER 4T API SG

Product Description:

United MX Super 4T motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of select high performance, high viscosity index base stocks and a special proprietary additive package. United MX Super 4T motorcycle oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity.

United MX Super 4T is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits:

- Reduces engine wear and extends engine life.
- Protects engine under severe operating conditions.
- Retards harmful deposit formation on vital engine parts.
- Protects against rust and corrosion.

Typical Characteristics:

Test Description	Method						
SAE Viscosity Grade	SAE J 300	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
Specific Gravity @ 15 °C	ASTM D 4052	0.878	0.882	0.886	0.888	0.885	0.893
Flash Point, °C	ASTM D 92	212	215	220	232	224	235
Pour Point, °C	ASTM D 97	-30	-27	-24	-18	-24	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	78.1	102	109	138	145	175
cSt @ 100°C	ASTM D 445	11.8	14.9	15.0	15.4	18.9	19.5
Viscosity Index	ASTM D 2270	145	152	143	115	148	128
TBN, mgKOH/g	ASTM D 2896	5.4	5.4	5.4	5.4	5.4	5.4
Color	ASTM D 1500	2.5	2.5	2.5	2.5	2.5	2.5

Specifications, Approvals & Recommendations:

- API SG
- JASO MA

Sheet

roduct