



UNITED UC110

Product Description:

United UC110 Grease is a heavy duty, water resistant, multi-purpose grease for automotive and light truck chassis applications. It is formulated with Calcium thickener, rust and oxidation inhibiting additives.

UC110 Grease is suitable for a wide variety of lubrication use. Recommended for motor vehicles & farm tractors chassis & suspension systems lubrication points, ball, shaft & universal joints and coil springs. Suitable for general automotive, industrial and agricultural lubrication of equipment, machine parts and automotive wheel bearings. Provides maximum protection against rust and corrosion with chassis that is exposed to severe water exposure. Protects against moisture contamination with excellent water resistance. Prevent dust and dirt from reaching into the moving parts. This product is not recommended for low temperature application, the recommended operating temperature range is 15°C to 70°C.

Applications / Benefits:

- Significantly less rust & corrosion due to effective protection from severe water exposure.
- Longersuspension, ball, shaft & universal joints and coil springs life due to low wear.
- Calcium based, making it compatible with the majority of grease used for chassis.
- Excellent resistance to water washout.
- No softening/leakage under vibrations & mechanical stress due to good mechanical stability.

Typical Characteristics:

Test Description	Method	
NLGI grade	SAE J 300	2.5#
Thickener type	-	Calcium Soap
Color		Red
Texture		Smooth
Dropping Point, oC	ASTM D-2265	100
Worked Penetration	ASTM D-217	265-295
Rust and Corrosion Test	ASTM D-1743	PASS
Water Wash-out	ASTM D-1264	PASS